THE TOUGHEST PERFORMER FOR YOUR FIELD

Solis C48

UNLOCK NEW POSSIBILITIES, ELEVATE PRODUCTIVITY

BEST IN INDUSTRY 5 YEARS WARRANTY

CELEBRATING 1,500,000 TRACTORS GLOBALLY

COST EFFICIENT MECHANICAL TRACTORS

MADE OF REAL STEEL

STRATEGIC COLLABORATION WITH YANMAR

THE TOUGHEST PERFORMER FOR YOUR FIELD

Solis

C48

FEATURES	C48
ENGINE	
Engine Type	STAGE V , Yanmar Make
HP Category	46
No. of Cylinders	4
Aspiration	Natural Aspirated
Cubic Capacity (cc)	2,190
Rated RPM	2800
Cold Start	Yes
Air Cleaner	Dry, 5 inch
Max Torque (Nm)	146.2
Exhaust	Downdraft
TRANSMISSION	
Drive	4WD
Gearbox	12F+12R Synchro
Front Axle	4WD
SPEED (FORWARD)	
Maximum Speed (Km/Hr)	25
Minimum Speed (Km/Hr)	1.58
BRAKES	
Brakes	Mechanical
Type of Actuation	Mechanical
Parking Brake	Independent Type
DIFFERENTIAL LOCK	
Differential Lock	Mechanical, Foot Operated
PTO	
PTO (RPM)	540/750
PTO (Actuation)	Electro Hydraulic
STEERING	
Steering	Power
ELECTRICAL	
Battery	80Ah
Alternator	12V, 55A
HYDRAULICS	
Hydraulic Lifting Capacity (Kg)	1450
3 Point Linkage	CAT-II
Stay Bars	Adjustable
Auxiliary Hydraulic Circuit	3DA
Lift Rods	Both Side Adjustable
Litre Per Minute (LPM)	30

FEATURES	C48
CAPACITY (LTRS)(+/-5%)	
Fuel Tank (Ltr.)	60
TURNING RADIUS	
Without Brakes (mm)	2700
TYRE	
Front	260/70 R16 RT 765
Rear	360/70 R24 RT 765
DIMENSION (+/-5%) (4WD/2WD)	
Weight (Kg)	1870
Overall Length (mm)	3470
Overall Width (mm)	1400 with Agri Tyre
Overall Height (mm) up to ROPS	2575
Wheel Base (mm)	1900
Min. Ground Clearance (mm)	360
Front Track (mm)	1130
Rear Track (mm)	1122
OTHERS	
Trailer Hitch - Option 1	E Mark Swinging Bar
Trailer Hitch - Option 2	E Mark Trailer Hitch
Front Tow Hook	Yes
OPTIONAL TYRES	
Tyres	8-18 6PR,13.6-24 TR 135 8PR
	8-18, 13.6-26
	9.5-16,13.6-26
	8-18 TR171 8PR TT,13.6-26 TR 171 8PR TT
	Front : 240/70 R16, Rear : 360/70 R24
	Front : 250/80 R16, Rear : 400/80 R24
	Front : 280/70 R18, Rear : 420/70R24
	Front : 8-18, Rear : 12.4-24
	Front : 7x16, Rear : 11.2-24
	Front : 31X15.5-15 Turf, Rear : 44 x 18-20
	Front : 280/70-R16, Rear : 420/70R24
	Front : 12.5/70-16, Rear : 19.5L-24
	Front : 7x16, Rear : 12.4-24
	Front : 12-16.5, Rear : 17.5L-24
	Front : 10-16.5, Rear : 17.5L-24

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

DEALER STAMP

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)
Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221
Fax:+91- 01882-522222 | Email: info@solisworld.com | URL: www.solistractors.com